

FusionServer V7 Product collection



xFusion Digital Technologies Co., Ltd.









1288H V7 (4 drives)

1288H V7 (8 drives)

1288H V7 (10 drives)

FusionServer 1288H V7 (1288H V7) is a new-generation 1U 2-socket rack server designed for Internet, Internet Data Center (IDC), cloud computing, enterprise applications, and telecom applications. It is also ideal for IT core services, virtualization, high-performance computing, distributed storage, big data processing, and other complex workloads. The 1288H V7 features low power consumption, high scalability and reliability, easy deployment, and simplified management.





High-Density Computing Power

- High-Density Computing Power,1U space accommodates 2 x 350 W CPUs and 32 x DDR5 DIMMs.
- Faster Connectivity for Faster Applications, PCIe 5.0 and 400 Gbit/s NIC interconnection are supported.
- · High-Speed Flash, Doubling the Performance, 32 x E1.s or 20 x E3.s SSDs provide smaller size and higher density.



High Reliability and Security

- Heat pipe based remote heat dissipation technology ensures better temperature adaptation, providing 50% better heat dissipation capability than a single heat sink.
- · The innovative AI memory fault self-healing ensures stable system running and reduces system downtime by 66%.
- · RoT-based secure boot ensures security everywhere.



Efficient Energy Saving

- Unique algorithm for the lowest power consumption of fans and CPUs: Ensures 5% to 10% lower server power consumption than the industry average.
- Industry-leading power supply technology for higher efficiency: Three core technologies improve power and efficiency, enabling the industry-leading power conversion rate and the power loss 12.5% lower than the industry average.
- Intelligent service awareness and dynamic load adjustment: Dynamically adjusts the CPU working frequency based on the actual service load.



- Automatic version push and upgrades can be completed without onsite attendance, improving upgrade efficiency by 20 times.
- 75% streamlined deployment steps are performed by tools, improving deployment efficiency by 10 times.
- Takeover of all vendors' servers, automatic asset location identification, and real-time tracking are supported, achieving 100% stocktaking accuracy.

Form Factor	1U rack server
Processor	1 or 2 x 4rd Gen Intel® Xeon® Scalable processors (Sapphire Rapids) with TDP up to 350 W per processor
Chipset	Emmitsburg PCH
Memory	32 x DDR5 DIMMs, with up to 4800 MT/s speed
Local Storage	Supports hot-swappable drives in the following configurations: • 10 x 2.5" drives (6–10 NVMe SSDs and 0–4 SAS/SATA drives, with a total number of 10 or less) • 10 x 2.5" SAS/SATA drives/SSDs (2–4 NVMe SSDs and 6–8 SAS/SATA drives, with a total number of 10 or less) • 10 x 2.5" SAS/SATA drives/SSDs • 8 x 2.5" SAS/SATA drives/SSDs • 4 x 3.5" SAS/SATA drives/SSDs • 32 x E1.s SSDs • 20 x E3.s SSDs* • 2 x M.2 SSDs
RAID	Provides RAID 0, 1, 10, 1E, 5, 50, 6, 60; supports optional supercapacitor for cache data power failure protection, RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration.
Network	Provides expansion capability of multiple types of networks. Supports OCP 3.0 NICs. The two FlexIO card slots support two OCP 3.0 NICs, which can be configured as required. Hot swap and PCIe 5.0 is supported.
PCIe Expansion	Provides 5 x PCIe slots, including 2 x FlexIO slots dedicated for OCP 3.0 NICs and 3 x PCIe slots, and 2 slots support PCIe 5.0
Fan Module	Provides 8 x hot-swappable counter-rotating fan modules in N+1 redundancy.
Power Supply	2 x hot-swappable PSUs in 1+1 redundancy mode. Supported options include: • 900 W AC Platinum/Titanium PSUs (input: 100 V to 240 V AC, or 192 V to 288 V DC) • 1500 W AC Platinum PSUs • 1000 W (input: 100 V to 127 V AC) • 1500 W (input: 200 V to 240 V AC, or 192 V to 288 V DC) • 1500 W 380 V HVDC PSUs (input: 260 V to 400 V DC) • 1200 W -48 V to -60 V DC PSUs (input: -38.4 V to -72 V DC) • 2000 W AC Platinum PSUs • 1800 W (input: 200 V to 220 V AC or 192 V to 200 V DC) • 2000 W (input: 220 V to 240 V AC, or 200 V to 288 V DC)
Management	The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0; provides a remote management user interface based on HTML5/VNC KVM; supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management. • It is optional to configure the FusionDirector management software that provides advanced management features such as five intelligent technologies and realizes intelligent, automated, visualized, and refined management through the lifecycle.
os	FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, Debian, openEuler
Security	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security panel, secure boot, and chassis cover opening detection
Operating Temperature	5°C to 50°C (41°F to 122°F), compliant with ASHRAE Classes A1, A2, A3, and A4
Certification	CE, UL, CCC, FCC, VCCI, and RoHS
Installation Suite	L-shaped guide rails, adjustable guide rails, and holding rails
Dimensions (H x W x D)	Chassis with 3.5" drives: 43.5 mm x 447 mm x 798 mm (1.71 in. x 17.60 in. x 31.42 in.) Chassis with 2.5" drives: 43.5 mm x 447 mm x 798 mm (1.71 in. x 17.60 in. x 31.42 in.) *According to the plan, it will be realized within 2023.











2288H V7 (8 drives)

2288H V7 (12 drives)

2288H V7 (24 drives)

2288H V7 (25 drives)

The FusionServer 2288 V7 (2288 V7) is a next-generation 2U 2-socket rack server designed for the Internet, Internet Data Center (IDC), cloud computing, enterprises business, and telecom. The 2288 V7 is also ideal for IT core services, virtualization, high-performance computing, distributed storage, big data processing, and other complex workloads. The 2288 V7 features low power consumption, high scalability and reliability, easy deployment, and simplified management.





Flexible Computing

- Lightweight Computing Power, Energy Saving and Consumption Reduction, Lower-power fans meet heat dissipation requirements, simplifying the air duct design and enabling fast heat dissipation.
- Streamlined Design, Flexible and Easy Use, Four riser-free standard PCle slots ensure flexible configuration and tool-free maintenance.



High Reliability and Security

- Heat pipe based remote heat dissipation technology ensures better temperature adaptation, providing 50% better heat dissipation capability than a single heat sink.
- The innovative AI memory fault self-healing ensures stable system running and reduces system downtime by 66%.
- · RoT-based secure boot ensures security everywhere.



Efficient Energy Saving

- Unique algorithm for the lowest power consumption of fans and CPUs: Ensures 5% to 10% lower server power consumption than the industry average.
- Industry-leading power supply technology for higher efficiency: Three core technologies improve power and efficiency, enabling the industry-leading power conversion rate and the power loss 12.5% lower than the industry average.
- Intelligent service awareness and dynamic load adjustment: Dynamically adjusts the CPU working frequency based on the actual service load.



- Automatic version push and upgrades can be completed without onsite attendance, improving upgrade efficiency by 20 times.
- 75% streamlined deployment steps are performed by tools, improving deployment efficiency by 10 times.
- Takeover of all vendors' servers, automatic asset location identification, and real-time tracking are supported, achieving 100% stocktaking accuracy.

Form Factor	2U rack server
Processor	1 or 2 x 4rd Gen Intel® Xeon® Scalable processors (Sapphire Rapids) with TDP up to 225 W per processor
Chipset	Emmitsburg PCH
Memory	16 x DDR5 DIMMs, delivering up to 4800 MT/s speed
Local Storage	Supports hot-swappable drives in the following configuration options: • 8 to 31 x 2.5" SAS/SATA/SSD drives • 10 to 14 x 3.5" SAS/SATA drives • 4 x NVMe SSDs • Up to 31 x 2.5" drives Supports flash storage: • 2 x M.2 SSDs
RAID	Supports RAID 0, 1, 10, 1E, 5, 50, 6, or 60, optional supercapacitor for cache data power failure protection, RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration.
Network	Expansion capability for multiple types of networks. Supports OCP 3.0 NICs are supported. One FlexIO card slot supports one OCP 3.0 NIC, which can be configured as required.
PCIe Expansion	Up to 8 x PCle slots 1 x FlexIO expansion slot dedicated for OCP3.0, 1 x expansion slot dedicated for the RAID controller card, and 6 x standard PCle expansion slots
Heterogeneous Accelerator Card	Up to 4 x 75 W half-height half-length GPU accelerator cards
Fan Module	4 x hot-swappable counter-rotating fans in N+1 redundancy
Power Supply	2 x hot-swappable PSUs in 1+1 redundancy mode. Supported options include: 900 W AC Platinum/Titanium PSUs (input: 100 V to 240 V AC, or 192 V to 288 V DC) 1500 W AC Platinum PSUs 1000 W (input: 100 V to 127 V AC) 1500 W (input: 200 V to 240 V AC, or 192 V to 288 V DC) 1500 W (input: 200 V to 240 V AC, or 192 V to 400 V DC) 1500 W 380 V HVDC PSUs (input: 260 V to 400 V DC) 1200 W -48 V to -60 V DC PSUs (input: -38.4 V to -72 V DC) 3000 W AC Titanium PSUs 2500 W (input: 200 V to 220 V AC) 2900 W (input: 220 V to 230 V AC) 3000 W (input: 230 to 240 V AC) 2000 W AC Platinum/Titanium PSUs 1800 W (input: 200 V to 220 V AC, or 192 V to 200 V DC) 2000 W (input: 220 V to 240 V AC, or 200 V to 288 V DC)
Management	The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management. • It is optional to configure the FusionDirector management software that provides advanced management features such as five intelligent technologies and realizes intelligent, automated, visualized, and refined management throughout the lifecycle.
os	FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, Debian, and openEuler
Security	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security panel, secure boot, and chassis cover opening detection
Operating Temperature	5°C to 40°C (41°F to 104°F), compliant with ASHRAE Classes A1, A2, A3, and A4
Certification	CE, UL, CCC, FCC, VCCI, and RoHS
Installation Suite	L-shaped guide rails, adjustable guide rails, and holding rails
Dimensions (H x W x D)	Chassis with 3.5" drives: 86.1 mm x 447 mm x 798 mm (3.39 in. x 17.60 in. x 31.42 in.) Chassis with 2.5" drives: 86.1 mm x 447 mm x 798 mm (3.39 in. x 17.60 in. x 31.42 in.)











2288H V7 (8 drives)

2288H V7 (12 drives)

2288H V7 (24 drives)

2288H V7 (25 drives)

The FusionServer 2288H V7 (2288H V7) is a new-generation 2U 2-socket rack server designed for the Internet, Internet Data Center (IDC), cloud computing, enterprise business, and telecom. It is also ideal for IT core services, virtualization, high-performance computing, distributed storage, big data processing, and other complex workloads. The 2288H V7 features low power consumption, high scalability and reliability, easy deployment, and simplified management.





Robust Performance

- Up to 350 W CPUs and 32 x DDR5 DIMMs provide strong computing power, based on Intel's latest Sapphire Rapids CPU, Up to 50% Better Overall Performance
- PCle 5.0 protocol and 17 x standard PCle slots ensure flexible configuration, 100% Higher PCle Bandwidth for High-Speed Interconnection
- High-Speed Flash Memory, Diverse Configurations: ①34 x NVMe U.2 SSDs, High-speed flash for high performance;
 ②36 x E1.s or 48 x E3.s SSDs, Smaller size, higher density; ③45 x SAS/SATA SSDs, More slots, more cost-effective



High Reliability and Security

- Heat pipe based remote heat dissipation technology ensures better temperature adaptation, providing 50% better heat dissipation capability than a single heat sink.
- The innovative AI memory fault self-healing ensures stable system running and reduces system downtime by 66%.
- · RoT-based secure boot ensures security everywhere.



Efficient Energy Saving

- Unique algorithm for the lowest power consumption of fans and CPUs: Ensures 5% to 10% lower server power consumption than the industry average.
- Industry-leading power supply technology for higher efficiency: Three core technologies improve power and efficiency, enabling the industry-leading power conversion rate and the power loss 12.5% lower than the industry average.
- Intelligent service awareness and dynamic load adjustment: Dynamically adjusts the CPU working frequency based on the actual service load.



- Automatic version push and upgrades can be completed without onsite attendance, improving upgrade efficiency by 20 times.
- · 75% streamlined deployment steps are performed by tools, improving deployment efficiency by 10 times.
- Takeover of all vendors' servers, automatic asset location identification, and real-time tracking are supported, achieving 100% stocktaking accuracy.

Form Factor	2U rack server
Processor	1 or 2 x 4rd Gen Intel® Xeon® Scalable processors (Sapphire Rapids) with TDP up to 350 W per processor
Chipset	Emmitsburg PCH
Memory	32 DDR5 DIMMs, with up to 4800 MT/s speed. Supports memory expansion via CXL with up to 16 x DDR5 or DDR4 DIMM slots; up to 48 x DIMM slots*
Local Storage	Hot-swappable drives with the following configuration options are supported: • 8 to 31 x 2.5" SAS/SATA/SSD drives • 12 to 20 x 3.5" SAS/SATA drives • 4/8/16/24 x NVMe SSDs • 36 x E1.s SSDs or 48 x E3.s SSDs • Up to 45 x 2.5" drives, or 34 x full NVMe SSDs • 2 x M.2 SSDs
RAID	RAID 0, 1, 10, 1E, 5, 50, 6, or 60; optional supercapacitor for cache data power failure protection, RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration.
Network	Expansion capability of multiple types of networks. OCP 3.0 NICs are supported. Both two FlexIO card slots support two OCP 3.0 NICs, which can be configured as required. Hot swap is supported.
PCIe Expansion	Up to 19 x PCIe slots: 2 x FlexIO slots dedicated for OCP 3.0 NICs and 17 x standard PCIe expansion slots, 14 slots support PCIe 5.0
GPU Card	4 x double-width GPU accelerator cards or 14 x single-width GPU accelerator cards
Fan Module	4 x hot-swappable counter-rotating fans in N+1 redundancy
Power Supply	2 x hot-swappable PSUs in 1+1 redundancy mode. Supported options include: • 900 W AC Platinum/Titanium PSUs (input: 100 V to 240 V AC, or 192 V to 288 V DC) • 1500 W AC Platinum PSUs 1000 W (input: 100 V to 127 V AC) 1500 W (input: 200 V to 240 V AC, or 192 V to 288 V DC) • 1500 W 380 V HVDC PSUs (input: 260 V to 400 V DC) • 1200 W -48 V to -60 V DC PSUs (input: -38.4 V to -72 V DC) • 3000 W AC Titanium PSUs 2500 W (input: 200 V to 220 V AC) 2900 W (input: 220 V to 230 V AC) 3000 W (input: 230 to 240 V AC) • 2000 W AC Platinum PSU 1800 W (input: 200 V to 220 V AC, or 192 V to 200 V DC) 2000 W (input: 220 V to 240 V AC, or 200 V to 288 V DC)
Management	The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management. • It is optional to configure the FusionDirector management software that provides advanced management features such as five intelligent technologies and realizes intelligent, automated, visualized, and refined management throughout the lifecycle.
os	FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, Debian, and openEuler
Security	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security panel, secure boot, and chassis cover opening detection
Operating Temperature	5°C to 50°C (41°F to 122°F), compliant with ASHRAE Classes A1, A2, A3, and A4
Certification	CE, UL, CCC, FCC, VCCI, and RoHS
Installation Suite	L-shaped guide rails, adjustable guide rails, and holding rails
Dimensions (H x W x D)	Chassis with 3.5" drives: 86.1 mm x 447 mm x 798 mm (3.39 in. x 17.60 in. x 31.42 in.) Chassis with 2.5" drives: 86.1 mm x 447 mm x 798 mm (3.39 in. x 17.60 in. x 31.42 in.) *According to the plan, it will be realized within 2023









Rear backplane of the 5288 V7 storage model

The FusionServer 5288 V7 (5288 V7) is a new-generation 4U 2-socket rack server designed for the Internet, Internet Data Center (IDC), cloud computing, enterprise business, and telecom. It is also ideal for IT core services, virtualization, high-performance computing, distributed storage, big data processing, and other complex workloads. The 5288 V7 features low power consumption, high scalability and reliability, easy deployment, and simplified management.





Ultra-large Storage

- Ultra-large Storage, 44 x 3.5-inch drives + 4 x NVMe U.2 SSDs
- Supreme Computing Power, Up to 350 W CPUs and 32 x DDR5 DIMMs provide strong computing power, based on Intel's latest Sapphire Rapids CPU.
- · Flexible Configuration, Up to 10 x standard PCIe expansion slots



High Reliability and Security

- Heat pipe based remote heat dissipation technology ensures better temperature adaptation, providing 50% better heat dissipation capability than a single heat sink.
- The innovative AI memory fault self-healing ensures stable system running and reduces system downtime by 66%.
- · RoT-based secure boot ensures security everywhere.



Efficient Energy Saving

- Unique algorithm for the lowest power consumption of fans and CPUs: Ensures 5% to 10% lower server power consumption than the industry average.
- Industry-leading power supply technology for higher efficiency: Three core technologies improve power and efficiency, enabling the industry-leading power conversion rate and the power loss 12.5% lower than the industry average.
- Intelligent service awareness and dynamic load adjustment: Dynamically adjusts the CPU working frequency based on the actual service load.



- Automatic version push and upgrades can be completed without onsite attendance, improving upgrade efficiency by 20 times.
- 75% streamlined deployment steps are performed by tools, improving deployment efficiency by 10 times.
- Takeover of all vendors' servers, automatic asset location identification, and real-time tracking are supported, achieving 100% stocktaking accuracy.

Form Factor	4U rack server
Processor	1 or 2 x 4rd Gen Intel® Xeon® Scalable processors (Sapphire Rapids) with TDP up to 350 W per processor
Chipset	Emmitsburg PCH
Memory	32 x DDR5 DIMMs, at 4800 MT/s
Local Storage	Hot-swappable drive configurations: • 8 to 48 x 2.5" SAS/SATA drives/SSDs • 24 to 44 x 3.5" SAS/SATA drives • 8 x NVMe SSDs • Support E1.s or E3.s SSDs* Flash storage: • 2 x M.2 SSDs
RAID	RAID 0, 1, 10, 1E, 5, 50, 6, or 60; optional supercapacitor for cache data power failure protection, RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration
Network	Expansion capability for multiple types of networks OCP 3.0 NICs are supported. The two FlexIO card slots support two OCP 3.0 NICs, which can be configured as required. Hot swap and PCIe 5.0 is supported.
PCle Expansion	Up to 10 x PCIe slots, including 2 x FlexIO slots dedicated for OCP 3.0 NICs and 10 x PCIe expansion slots, PCIe 5.0 is supported.
GPU Card	10 x FHFL single-width GPU accelerator cards
Fan Module	6 or 8 x hot-swappable counter-rotating fans in N+1 redundancy
Power Supply	2 x hot-swappable PSUs in 1+1 redundancy mode. Supported options include: • 900 W AC Platinum/Titanium PSUs (input: 100 V to 240 V AC, or 192 V to 288 V DC) • 1500 W AC Platinum PSUs 1000 W (input: 100 V to 127 V AC) 1500 W (input: 200 V to 240 V AC, or 192 V to 288 V DC) • 1500 W 380 V HVDC PSUs (input: 260 V to 400 V DC) • 1200 W -48 V to -60 V DC PSUs (input: -38.4 V to -72 V DC) • 3000 W AC Titanium PSUs 2500 W (input: 200 V to 220 V AC) 2900 W (input: 220 V to 230 V AC) • 2000 W AC Platinum PSUs 1800 W (input: 200 V to 220 V AC, or 192 V to 200 V DC) 2000 W (input: 220 V to 240 V AC, or 200 V to 288 V DC)
Management	The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management. • It is optional to configure the FusionDirector management software that provides advanced management features such as five intelligent technologies and realizes intelligent, automated, visualized, and refined management throughout the lifecycle.
os	FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, Debian, and openEuler
Security	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security panel, secure boot, and chassis cover opening detection
Operating Temperature	5°C to 35°C (41°F to 95°F), compliant with ASHRAE Classes A1, A2, A3, and A4
Certification	CE, UL, CCC, FCC, VCCI, and RoHS
Installation Suite	L-shaped guide rails, adjustable guide rails, and holding rails
Dimensions (H x W x D)	Chassis with 3.5" drives: 175 mm × 447 mm × 798 mm (6.89 in. x 17.60 in. x 31.42 in.)







G5200 V7 rear backplane

FusionServer G5200 V7 (G5200 V7) is a new-generation 4U 2-socket GPU server that meets AI requirements of large-capacity storage. Featuring robust performance, high reliability and security, efficient energy saving, simplified management, and easy deployment, it can be used for training and inference workloads and is suitable for voice, image, and video analysis scenarios.





Robust Performance

- Ultra-large storage: up to 32 x 3.5-inch SAS/SATA drives, 4 x NVMe SSDs, and 2 x M.2 SSDs
- Supreme computing power: up to 350 W CPUs based on Intel's latest Sapphire Rapids platform; 4 x FHFL double-width GPU cards; GPU pass-through design eliminates the need of PCIe switches for communication between CPUs and GPUs.
- Flexible expansion: up to 10 x standard PCle slots and 2 x OCP 3.0 NICs



High Reliability and Security

- Heat pipe based remote heat dissipation technology ensures better temperature adaptation, providing 50% better heat dissipation capability than a single heat sink.
- · The innovative AI memory fault self-healing ensures stable system running and reduces system downtime by 66%.
- · RoT-based secure boot ensures security everywhere.



Efficient Energy Saving

- Unique algorithm for the lowest power consumption of fans and CPUs: Ensures 5% to 10% lower server power consumption than the industry average.
- Industry-leading power supply technology for higher efficiency: Three core technologies improve power and efficiency, enabling the industry-leading power conversion rate and the power loss 12.5% lower than the industry average.
- Intelligent service awareness and dynamic load adjustment: Dynamically adjusts the CPU working frequency based on the actual service load.



- Automatic version push and upgrades can be completed without onsite attendance, improving upgrade efficiency by 20 times.
- 75% streamlined deployment steps are performed by tools, improving deployment efficiency by 10 times.
- Takeover of all vendors' servers, automatic asset location identification, and real-time tracking are supported, achieving 100% stocktaking accuracy.

Form Factor	4U GPU server
Processor	1 or 2 x 4th Gen Intel® Xeon® Scalable processors (Sapphire Rapids) with TDP up to 350 W per processor
Chipset	Emmitsburg PCH
Memory	32/16 x DDR5 DIMMs, with up to 4800 MT/s speed
Local Storage	Supports hot-swappable drives in the following configurations: • Up to 32 x 3.5-inch SAS/SATA drives • Up to 4 x NVMe SSDs • Support E1,s SSDs* • 2 x M.2 SSDs
RAID	RAID 0, 1, 10, 1E, 5, 50, 6, or 60; Supercapacitors for cache data protection from power failures; RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration
GPU Card	4 x FHFL dual-width GPU cards, 10 x single-width GPU cards
Network	Multiple network expansion capabilities; 2 x OCP 3.0 NICs, which can be configured as required and supports orderly hot swap, support PCle 5.0
PCle Expansion	Up to 10 x standard PCle slots, support PCle 5.0
Fan Module	8 x hot-swappable counter-rotating fan modules in N+1 redundancy
PSU	4 x hot-swappable PSUs in N+N/N+M redundancy 1500 W AC Platinum PSUs 1000 W (input: 100 V to 127 V AC) 1500 W (input: 200 V to 240 V AC, or 192 V to 288 V DC) 1500 W 380 V HVDC PSUs (input: 260 V to 400 V DC) 1200 W -48 V to -60 V DC PSUs (input: -38.4 V to -72 V DC) 3000 W AC Titanium PSUs 2500 W (input: 200 V to 220 V AC) 2900 W (input: 220 V to 230 V AC) 3000 W (input: 230 to 240 V AC) 2000 W AC Platinum PSUs 1800 W (input: 200 V to 220 V AC, or 192 V to 200 V DC) 2000 W (input: 220 V to 240 V AC, or 200 V to 288 V DC)
Management	The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0; provides a remote management user interface based on HTML5/VNC KVM; supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management. • Can be configured with the FusionDirector management software to provide advanced management features such as five intelligent technologies, enabling intelligent, automatic, visualized, and refined management through the lifecycle.
os	FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, Debian, and openEuler
Security	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security panel, secure boot, and chassis cover opening detection
Operating Temperature	5°C to 35°C (41°F to 95°F) (compliant with ASHRAE Class A1/A2/A3)
Certification	CE, UL, CCC, FCC, VCCI, and RoHS
Installation Suite	L-shaped guide rails, adjustable guide rails, and holding rails
Dimensions (H x W x D)	175 mm x 447 mm x 798 mm (6.89 in. x 17.60 in. x 31.42 in.)







X6000 V7 (drives)

X6000 V7 (drives)

The FusionServer X6000 V7 is a new-generation 2U high-density server that is rearchitected for serving Internet service provider (ISP) and high-performance computing (HPC) customers to meet their demands on large-scale server deployment. The servers apply to Internet, HPC, cloud computing, and data center applications, as well as software-defined storage (SDS), big data, and software-defined infrastructure (SDI).





Extreme Heat Dissipation, Achieving Peak Computing Power Density

- Houses 8 x 4th Gen Intel® Xeon® Scalable processors in a 2U space with TDP up to 350 W
- Accommodates up to 5 x air-cooled servers (after power supply reconstruction) or up to 18 x liquid-cooled servers in a chassis



Robust Power Supply, Giving a High-Reliability Assurance

- Houses 4 x 3000 W PSUs in a 2U space, the only one in the industry
- Provides PSUs in 2+2 redundancy mode in a 2U space, the only one in the industry
- Supports stable operation of four nodes with one PSU and provides shared backplanes
- Uses 80 PLUS Titanium PSUs that provide a conversion efficiency of up to 96.5%



New-Generation Architecture, Higher Performance and Bandwidth

- Uses new-generation architecture, improving the system performance by up to 59%
- Supports 4 x UPI 2.0 links, increasing the cross-CPU access performance by about 30%
- · Provides a maximum memory capacity of 16 TB and DDR5
- Supports PCIe 5.0 full ports, which doubles the network bandwidth

Form Factor	2U 4-node chassis
Server Node	4 x 1U half-width 2-socket server nodes
PSU	4 x hot-swappable 1500W, 2000W, or 3000W AC PSUs in 1+1, 3+1, or 2+2 redundancy mode (Configured based on the power consumption of the server and a single PSU.)
Power Supply	100V to 240V AC, 240V DC
Fan Module	4 x hot-swappable 8080++ fan modules in N+1 redundancy mode
Operating Temperature	5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4
Certification	CE, UL, FCC, CCC, VCCI, and RoHS
PCIe expansion	A node supports a maximum of four PCIe expansion slots, including one built-in RAID controller card slot, one FlexIO expansion slot dedicated for OCP3.0 NICs, and two standard PCIe expansion slots
Dimensions (H x W x D)	447 mm \times 899 mm \times 86.1 mm (17.60 in. x 35.39 in. x 3.39 in.)

Introduction



The FusionServer XH321 V7 is a new-generation 1U half-width 2-socket server node of xFusion, innovatively designed to break through energy constraints and improve system computing power densitylt features powerful heat dissipation, ultra-high computing power density, highly reliable power supply system, and increased performance and bandwidth. It is ideal for multiple application scenarios such as data centers, cloud computing, big data, and the Internet.





High-Density Computing Power and Superior Performance

- Up to 2 x 4th Gen Intel[®] Xeon[®] Scalable processors with TDP up to 350W
- Up to 16 x 4800 MT/s DDR5 DIMMs and up to 4096 GB memory capacity
- NVMe SSDs for acceleration and 2+4 balanced configuration, eliminating I/O bottlenecks
- · 2 x M.2 SSDs that function as high-speed and reliable OS boot drives



Robust Reliability

- · 3000W highly reliable PSUs and hot swap maintenance
- RAID cache and supercapacitors for data protection from power failures

Processor 2 x 4th Gen Intel® Xeon® Scalable processors with 350W TDP per processor Memory Slot 16 x DDR4/DDR5 DIMM slots, and up to 4096 GB memory (configured with 256 GB DDR5 DIMMs) at 4800 MT/s Local Storage Up to 6 x 2.5-inch SAS/SATA/SSD/NVMe drives. NVMe drives support 2+4 balanced configuration Up to 2 x M.2 2280 or 2242 SATA SSDs Mixed configurations of different types of drives RAID RAID 0, 1, 5, 6, 10, or 50 and supercapacitor for power failure protection M.2 SSDs in RAID 0, 1, or 5 PCIe Expansion 2 x PCIe 4.0 or PCIe 5.0 x16 half-height half-length (HHHL) expansion slots OCP Expansion 1 x OCP 3.0 expansion slot, support PCIe 5.0 ** The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. The iBMC supports standard interfaces such as Redfish, SMMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. ** Four compute nodes can be aggregated into one management port to simplify management. * It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware upgrade, realizing intelligent and automatic management throughout the lifecycle. Supported OS FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, oracle, Ubuntu, and Debian <th< th=""><th>Form Factor</th><th>1U half-width 2-socket server node</th></th<>	Form Factor	1U half-width 2-socket server node
Local Storage Up to 6 x 2.5-inch SAS/SATA/SSD/NVMe drives. NVMe drives support 2+4 balanced configuration Up to 2 x M.2 2280 or 2242 SATA SSDs Mixed configurations of different types of drives RAID RAID 0, 1, 5, 6, 10, or 50 and supercapacitor for power failure protection M.2 SSDs in RAID 0, 1, or 5 PCIe Expansion 2 x PCIe 4.0 or PCIe 5.0 x16 half-height half-length (HHHHL) expansion slots OCP Expansion 1 x OCP 3.0 expansion slot, support PCIe 5.0 • The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. • Four compute nodes can be aggregated into one management port to simplify management. • It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware upgrade, realizing intelligent and automatic management throughout the lifecycle. Supported OS Discontinual Centrols, Oracle, Ubuntu, and Debian Cettification CE, UL, FCC, CCC, VCCI, and RoHS	Processor	2 x 4th Gen Intel® Xeon® Scalable processors with 350W TDP per processor
Up to 2 x M.2 2280 or 2242 SATA SSDs Mixed configurations of different types of drives RAID RAID 0, 1, 5, 6, 10, or 50 and supercapacitor for power failure protection M.2 SSDs in RAID 0, 1, or 5 PCIe Expansion 2 x PCIe 4.0 or PCIe 5.0 x16 half-height half-length (HHHL) expansion slots OCP Expansion 1 x OCP 3.0 expansion slot, support PCIe 5.0 • The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. • Four compute nodes can be aggregated into one management port to simplify management. • It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware upgrade, realizing intelligent and automatic management throughout the lifecycle. Supported OS FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, and Debian Operating Temperature 5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4 Certification CE, UL, FCC, CCC, VCCI, and RoHS	Memory Slot	
M.2 SSDs in RAID 0, 1, or 5 PCIe Expansion 2 x PCIe 4.0 or PCIe 5.0 x16 half-height half-length (HHHL) expansion slots 1 x OCP 3.0 expansion slot, support PCIe 5.0 • The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. • Four compute nodes can be aggregated into one management port to simplify management. • It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware upgrade, realizing intelligent and automatic management throughout the lifecycle. Supported OS FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, and Debian Operating Temperature 5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4 CE, UL, FCC, CCC, VCCI, and RoHS	Local Storage	Up to 2 x M.2 2280 or 2242 SATA SSDs
1 x OCP 3.0 expansion slot, support PCle 5.0 • The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. • Four compute nodes can be aggregated into one management port to simplify management. • It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware upgrade, realizing intelligent and automatic management throughout the lifecycle. Supported OS FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, and Debian Operating Temperature 5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4 Certification CE, UL, FCC, CCC, VCCI, and RoHS	RAID	
The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. Four compute nodes can be aggregated into one management port to simplify management. It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware upgrade, realizing intelligent and automatic management throughout the lifecycle. FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, and Debian Operating Temperature 5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4 CE, UL, FCC, CCC, VCCI, and RoHS	PCIe Expansion	2 x PCle 4.0 or PCle 5.0 x16 half-height half-length (HHHL) expansion slots
management features such as fault diagnosis, automatic O&M, and hardware security hardening. The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. Four compute nodes can be aggregated into one management port to simplify management. It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware upgrade, realizing intelligent and automatic management throughout the lifecycle. Supported OS FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, and Debian Operating Temperature 5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4 CE, UL, FCC, CCC, VCCI, and RoHS	OCP Expansion	1 x OCP 3.0 expansion slot, support PCIe 5.0
Linux, CentOS, Oracle, Ubuntu, and Debian Operating Temperature 5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4 Certification CE, UL, FCC, CCC, VCCI, and RoHS	Management	 management features such as fault diagnosis, automatic O&M, and hardware security hardening. The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management interface based on HTML5/VNC KVM, and supports CD-free deployment and Agentess for smart and simplified management. Four compute nodes can be aggregated into one management port to simplify management. It is optional to configure the FusionDirector management software that provides advanced management functions such as stateless computing, batch OS deployment, and automatic firmware
Certification CE, UL, FCC, CCC, VCCI, and RoHS	Supported OS	
	Operating Temperature	5°C to 45°C (41°F to 113°F), compliant with ASHRAE Classes A1 to A4
Dimensions (H x W x D) 218.7 mm x 632 mm x 40.7 mm (8.61 in. x 24.88 in. x 1.60 in.)	Certification	CE, UL, FCC, CCC, VCCI, and RoHS
	Dimensions (H x W x D)	218.7 mm x 632 mm x 40.7 mm (8.61 in. x 24.88 in. x 1.60 in.)

xFusion Digital Technologies Co., Ltd. Consulting telephone: 400-080-6888 Technical hotline: 400-009-8999

Address: 9th Floor, Building 1, Zensun Boya Square, Longzihu Wisdom Island,

Zhengdong New District, Zhengzhou, Henan Province

Website: www.xfusion.com



Copyrights © xFusion Digital Technologies Co., Ltd 2022. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of xFusion Digital Technologies Co., Ltd.

Trademarks and Permissions

CEPUSION and other xFusion trademarks are trademarks of xFusion Digital Technologies Co., Ltd. All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

In this document, "xFusion" is used to refer to "xFusion Digital Technologies Co., Ltd." for concise description and easy understanding, which does not mean that "xFusion" may have any other meaning. Any "xFusion" mentioned or described hereof may not be understood as any meaning other than "xFusion Digital Technologies Co., Ltd.", and xFusion Digital Technology Co., Ltd. shall not bear any liability resulting from the use of "xFusion".

The purchased products, services and features are stipulated by the contract made between xFusion and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied. The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.